



259.95 EUR
incl. 19% VAT, plus [shipping](#)

- Intel Q470 Chipset !
- Intel vPro tech support !
- Support triple display !
- ATX Powered !



- Up to Intel® Comet Lake 10th i9 35W & i5 95W LGA processor
- Intel® Q470 Chipset
- Intel® vPro technology support
- 2 x DDR4 SO-DIMM up to 32GB
- Support triple display for HDMI, DisplayPort and LVDS/eDP
- 1 x M.2 M 2280, 1 x M.2 E 2230, 1 x mPCIe Full size, 1 x PCIe X16
- 2 x Intel® Gigabit Ethernet
- ATX

MECHANICAL

FORM FACTOR

Mini-ITX: 6.7" x 6.7" (170 mm x 170 mm)

SYSTEM	PROCESSOR	10th Gen Intel® Comet Lake LGA1200 Socket Processor / 10core TDP Max 35W / 8ccore TDP 65W / (ATX support 6core 95W)	
	CHIPSET	Intel® Q470 (Support RAID 0 / 1 / 5, VPro) / colay H420E	
	SYSTEM MEMORY	DDR4 2933/2666/2400MHz / 2 x 260-pin SO-DIMM / Max. 64 GB (Non-ECC)	
	GRAPHICS	Intel® HD Graphics	
	ETHERNET	Intel® I219-LM Giga LAN + Intel® I210-AT Giga LAN	
	AUDIO	Realtek® ALC662 / ALC888	
	I/O CHIPSET	Nuvoton NCT6126D(eSPI)	
	TPM	Nuvoton NPCT750AAAYX TPM2.0 (Optional)	
	EXPANSION SLOT	1 x M.2 2230 E key(PCle / USB) / PCIe 3.0 X16 slot / M.2 2242 / 2280 M key (PCle, SATA) / Mini PCIe Full size (PCle / USB / SATA)	
	GRAPHICS	BIOS	AMI BIOS / 256 Mbit SPI
H/W MONITOR		Temperature Monitor / Voltage Monitor / Fan Monitor	
WATCHDOG TIMER		1~255 steps by software program	
SMART FAN CONTROL		CPU Fan / System Fan	
2nd DISPLAYPORT		-	
VGA		-	
DVI		-	
HDMI		Up to 4K (4096 x 2160) @30 Hz	
DISPLAYPORT		Up to 4K (4096 x 2304) @60 Hz	
LVDS		Up to 1920 x 1200 @60 Hz	
REAR I/O	eDP (Option)	Up to 4K (4096 x 2304) @60 Hz	
	USB	4 x USB 2.0 / 4 x USB 3.2 Gen 2 (Q470)	
	DISPLAY I/O	1 x HDMI 1.4 / 1 x DisplayPort 1.2	
	AUDIO I/O	1 x Mic-in / 1 x Line-out / 1 x Line-in	
	LAN I/O	2 x RJ-45	
	SERIAL PORT	2 x RS232 (one support RS422,/485)	
	PS/2 PORT	-	
	OTHERS	-	
	STORAGE	2 x SATAIII	
	USB	1 x USB 3.0 / 2 x USB 2.0	
INTERNAL CONNECTORS	DISPLAY I/O	1 x LVDS (*Optional eDP SKU available) / 1 x Backlight Connector	
	AUDIO I/O	-	
	SERIAL PORT	-	
	PARALLEL PORT	-	
	GPIO	1 x MiAPI Header (Programmable. Support 10-bit GPIO)	
	FAN	1 x 4-pin CPU Fan Header / 1 x 4-pin System Fan Header	
	POWER	1 x ATX Power Connector / 1 x AT / ATX Mode Select Jumper / ATX 12V Power Connector (24-pin + 4-pin)	
	OTHERS	1 x CMOS Jumper / 1 x Front Audio Header (Mic-in & Line-out) / 1 x panel power select header / 1x buzzer header / 1 x SPDIF	
	POWER REQUIREMENT	POWER INPUT	ATX 24-pin + 4-pin

ENVIRONMENTAL	OPERATING TEMPERATURE	0 ~ 60°C (32 ~140°F)
	STORAGE TEMPERATURE	-40 ~ 85°C (-40 ~185°F)
	OPERATING HUMIDITY	10% ~ 95% R/H (Non-condensing)
	CERTIFICATION	CE / FCC Class B
OS	OS SUPPORT	Windows® 10 64-bit / Linux (support by request)
PACKING LIST	PACKAGE	1 x Motherboard / 1 x 50 cm SATA Cable / 1 x Quick Installation Guide / 1 x I/O Bracket (Full Height)