279.00 EUR
incl. 19% VAT, plus shipping

- Quad-Channel !



Support: Datasheet

The DarkCrystal SD Capture Mini-PCIe Quad is capable of preserving up to four channels simultaneously from multiple input sources. The exclusive hardware design of the DarkCrystal SD Capture Mini-PCIe Quad guarantees a fast response and solid performance for high-density SD capture or encoding demands. Saving you cost and a valuable slot on your PC.
The exclusive hardware design of the DarkCrystal SD Capture Mini-PCIe Quad guarantees a fast response and solid performance for high-density SD capture and encoding demands. All while saving a valuable slot on your PC.

- Video capture with composite input
- 4-channel concurrent capture solution
- Standard minicard dimension
- Mainstream programming languages supported
- DirectShow compatible

Module Type	**PCI Express Minicard**
Input	**4-ch Composite** **Audio(L/R)**
Video Resolution	**NTSC (29.97Hz): 720 x 480, 640 x 480, 360 x 240, 320 x 240, 180 x 120, 160 x 120** **PAL (25Hz): 720 x 576, 640 x 480, 360 x 288, 180 x 144**
Color Adjustment	**Brightness, Contrast, Hue (NTSC only), Saturation**
Operating Environment	**Temperature: 0 to +55 ■** **Humidity: 0 to 90% RHNC**
Storage Environment	**Temperature: -30 to +65 ■** **Humidity: 0 to 90% RHNC**
Power Requirement	**1.2W**
Dimensions (L x W)	**50.95 x 30mm**
System Requirements	
CPU	**Intel® Pentium®4 3.0 GHz** **AMD AthlonTM 64 3200+**
Memory	**512 MB RAM**
VGA	**VGA card with support for DirectX9.0c or above**
Sound Card	**Yes**

Supported OS	**Windows 7/8.1/10 (32/64 bits), Linux (32/64 bits)***