

339.00 EUR

incl. 19% VAT, plus [shipping](#)

- Intel Elkhart Lake SoC !
- 2x LAN !



- Intel Elkhart Lake SoC Processor
- 1* DDR4 3200MHz SO-DIMM up to 32GB
- 1* HDMI, 2* USB3.1, 1* USB-C, 2* RJ45, 1* COM
- Support 9~36V wide voltage input
- DC12V_40W Adapter

| | | |
|--------------------|---|--|
| Model | - HBFBP01-6210-B - HBFBP011-6210-B (WiFi model) | |
| CPU/Chipset | - Intel® Elkhart Lake SoC Processor | |
| BIOS | - AMI Flash ROM | |
| Memory | - 1* DDR4 3200MHz Dual Channel SO-DIMM up to 32GB | |
| Storage | - 1* M.2 M-key (2242, PCIe Gen.3 x2/SATA interface) support NVMe | |
| Expansion | - 1* M.2 E-key (2230, PCIe Gen.3 x1/USB2.0 interface) | |
| Rear Panel I/O | - 2* RJ45 - 1* DC-in - 1* HDMI - 2* USB3.1(Gen.2) A Type - 1* USB3.1(Gen.2) C Type | |
| Front Panel I/O | - 1* Power button + Power LED - 1* RS232/422/485 | |
| Internal Connector | - 1* GPIO - 2* USB2.0 | |
| Power Source | - Adapter : AC 90~240V input / DC12V_40W output / Lock type - System : DC9~36V input support | |
| Compliance | - CE, FCC, LVD, RoHS, ErP Ready | |
| Dimensions | - System: 125 (W) x 109 (D) x 44.5 (H) mm - Color Box : 158 (W) x 167 (D) x 123.6 (H) mm | |

| | |
|-------------|--|
| Temperature | <ul style="list-style-type: none">- Operating Temperature: -20 ~ 60° C (Under the condition of using M.2 interface SSD)- Storage Temperature: -40 ~ 85° C- Humidity: 10% ~ 95% RH @40°C (non-condensing) |
| OS Support | <ul style="list-style-type: none">- Windows 11, Linux |