




999.00 EUR

incl. 19% VAT, plus shipping

- DirectX 11!
- VIA VX11H MSP!
- Mini-ITX!
- Advanced I/O!



Hardware

Based on the Mini-ITX form factor measuring 17cm x 17cm, the VIA EPIA-M920 comes with a rich set of I/O and connectivity features, including two HDMI ports, one VGA port, two 18/24-bit LVDS connectors, three USB 3.0 ports, six USB 2.0 ports, and support for up to four COM ports.

Software

The EPIA-M920 is compatible with Microsoft Windows 10 IoT, Windows 10, Windows 8.1, Windows 8, Windows 7, WES7, and Windows XP, as well as most popular Linux distributions. A wide range of software development tools are also available, including the VIA Smart ETK.

Expandability

Storage

The functionality of the VIA EPIA-M920 can be further enhanced with the integration of an optional high-speed Wi-Fi module and I/O expansion cards supporting up to four COM ports.

2 SATA connectors

	Model Name	EPIA-M920
		-20Q: 2.0GHz VIA QuadCore E-Series (With Fan)
Processor		-16QE: 1.6GHz VIA Eden X4 (Fanless)
		-10E: 1.0GHz VIA Eden X2 (Fanless)
Chipset		VIA VX11H Media System Processor
BIOS		AMI Aptio UEFI BIOS, 4Mbit Flash memory
System Memory		2 DDR3 1333 SODIMM slots
		Up to 8GB memory per slot

Marial Name



[http://www.cartft.com/catalog/il/593]



Graphics

LAN Audio Super I/O

Expansion I/O

Onboard I/O

Back Panel I/O

Power Supply Operating System

System Monitoring and Management

Operating Temperature Operating Humidity Form Factor

Compliance

Integrated C-640 DX11 3D/2D graphics with MPEG-2, WMV9, VC1

and H.264 video decoding acceleration

Realtek RTL8111G (EPIA-M920-10E: VIA VT6130)

VIA VT2021 High Definition Audio Codec

Fintek F71869E 1 PCIe x4 slot

2 SATA connectors

2 SATA DOM power selectors1 USB 3.0 pin header for 1 port2 USB 2.0 pin headers for 4 ports

1 Dual channel 18/24-bit LVDS panel connector1 Single channel 18/24-bit LVDS panel connector

3 COM port pin headers (powered with selectable 5V/12V)

1 LPC pin header1 SMBus pin header1 S/PDIF-out connector

1 Digital I/O pin header (4 GPI + 4 GPO)1 Front audio pin header for Line-out, Mic-in

2 Smart Fan pin headers for CPU and system

2 Backlight control connectors for inverter power and brightness control

1 SD card (SDHC/SDXC) pin header

1 ATX power connector

1 PCIe x4 slot 2 USB 3.0 ports 2 USB 2.0 ports 2 HDMI ports 1 VGA port

1 COM (powered with selectable 5V/12V)

2 Gigabit Ethernet ports

3 Audio jacks: Line-in, Line-out, and Mic-in

2 PS/2 keyboard/mouse ports

ATX power connector

Windows 10 / 8.1 / 8 / 7, Win 10 IoT, WES 7, Linux, POSReady 7 Wake-on-LAN, Keyboard Power-on, Timer Power-on, System power management, AC power failure recovery, Watchdog Timer

0°C ~ 60°C

0% ~ 95% (non-condensing) Mini-ITX (17cm x 17cm, 6.7" x 6.7")

CE/FCC