

198.00 EUR
incl. 19% VAT, plus [shipping](#)

- Pico-ITX
- SATA
- DDR-II !
- 1 Ghz CPU



| | |
|---------------|--|
| Model | VIA EPIA PX1000G |
| Processor | VIA C7 1.0 GHz - Socket Nano25G4 |
| Chipset | VIA V3700 Unified Digital Media GSP Chipset |
| System Memory | 1 DDR2 512 3200MHz module Up to 1GB memory size |
| GPU | Integrated VIA UniChrome Pro3 3200G GSP graphics with MPEG-2/4 and WMV9 decoding acceleration |

| | |
|-------------------------|---|
| Onboard IDE | 1 LInkDMA 133/100MHz connector (2.0mm 44-pin header) |
| Onboard Serial ATA | 1 SATA connector |
| Onboard LAN | 1 VIA VT6102G 10/100Mbps Ethernet controller with Power Managemen System |
| Onboard Audio | VIA VT1708A High Definition Audio Codec |
| Internal I/O Connectors | <p>4 USB pin headers for 4 USB 2.0 ports</p> <ul style="list-style-type: none"> • 1 COM port connector • 1 PS2 mouse/keyboard pin header • 1 LVDS/DVI connector • 1 Multimedia connector to support external TV-out interface, Video capture port interface and Low pin count interface • 1 Audio pin header for line-out, line-in, mic-in, S/PDIF in, and 7.1 channels audio output • 1 Fan pin header for CPU fan • 1 Pico-ITX power connector |
| External I/O Ports | <p>1 RJ-45 LAN port</p> <ul style="list-style-type: none"> • 1 VGA port |
| BIOS | <p>Award BIOS</p> <ul style="list-style-type: none"> • 4/8Mbit flash memory |
| Management | <p>CPU temperature reading (manufacturing option)</p> <ul style="list-style-type: none"> • Watch Dog Timer (manufacturing option) • Keyboard-Power-on, Timer-Power-on • Wake-on-LAN • System power management • AC power failure recovery |
| Operating Temperature | 0°C - 50°C |
| Operating Humidity | 0% - 95% (relative humidity, non-condensing) |
| Form Factor | • Pico-ITX 10 cm x 7.2 cm |